

RS232 ↔ RS422/RS485 isolated converter



AD400Ei accessories



- Self RS485 line turn-around
- 1500 Veff galvanic isolation
- Speed up to 250 Kbps
- SUB D9 connector for RS232 port

- Screw-in terminal for RS422/485 port
- Metal casing, industrial CE standards
- LED signal display
- M.T.B.F. > 300.000 P.O.H.

AD400Ei



Designed to connect directly to PCs, this converter has a female SUB D9 connector to the RS232 port and a screw-in connecting terminal for the RS-422/485 port.

Its advanced technology provides speeds of 250 Kbps, making it ideal for the fast RS232 ports on modern computers.

5-YEAR WARRANTY

The high level of integration and built-in protection make the AD400Ei extremely reliable and compact.

The technical characteristics make it a universal product at a very attractive price.

SPECIFICATIONS

Conversion	RS232 to RS422 or RS485 with automatic (or software) RS485 turnaround, line polarization and termination via miniature jumpers
Speed	Up to 250 Kbps
Connections	Female SUB D 9 connector to the RS232 port and a screw-in connecting terminal for the RS422/485
Signaling	TxD and RxD signal display on LEDs
Power	From an external source (between +4.7VDC and +5.5VDC) or from the mouse, keyboard or USB port, symmetrical jack for left or right side connection, optional remote power supply
Fan-out	128 RS485 interfaces in homogenous network
Protections	HF Filtration, DES IEC801-2 protection, level 4, max. 15KV Surge protection by "transient voltage suppressors", 0.3 KW 8/20 μ S, 1500 Veff galvanic isolation
Consumption	150 mA, 32 RS485 interfaces with termination (maximum)
Environment	Operating temperature between 0°C and +65°C Relative humidity 95% to +25°C
Dimensions	73 mm (L) x 31 mm (l) x 14.8 mm (H), 31 g.
Accessories	A miniature screw-driver and a cable for external power, from the keyboard or mouse, are supplied

Reference to order

AD400Ei RS232 ↔ RS422/485 isolated converter with self line turn-around

Preconfigured versions available for quantity orders (remote power supply ...)

All trademarks mentioned are registered trademarks. ACKSYS is always looking to improve its products. The present specifications may be modified without notice and the specified characteristics do not represent contractual obligations.
All products are designed and manufactured in France.